

# .env

- [Our default .env file](#)

# Our default .env file

Sometimes you may break or not get the .env included in the zip, I'm hoping to resolve this soon:

This is the default .env.example which is renamed to .env

```
APP_NAME=Ticaga
APP_ENV=production
APP_KEY=
APP_DEBUG=false
APP_URL=

DEFAULT_DEPARTMENT=

LOG_CHANNEL=stack
LOG_DEPRECATIONS_CHANNEL=null
LOG_LEVEL=debug

DB_CONNECTION=mysql
DB_HOST=127.0.0.1
DB_PORT=3306
DB_DATABASE=ticaga
DB_USERNAME=
DB_PASSWORD=

BROADCAST_DRIVER=log
CACHE_DRIVER=file
FILESYSTEM_DISK=local
QUEUE_CONNECTION=sync
SESSION_DRIVER=database
SESSION_LIFETIME=120

MEMCACHED_HOST=127.0.0.1

REDIS_HOST=127.0.0.1
REDIS_PASSWORD=null
REDIS_PORT=6379
```

MAILERSEND\_API\_KEY=

#####

#

# How to change your email settings:

# - smtp :: SMTP Emails

# - mailersend :: MailerSend

#

#####

MAIL\_ENABLED=false

MAIL\_MAILER=smtp

MAIL\_HOST=smtp-relay.brevo.com

MAIL\_PORT=587

MAIL\_USERNAME=

MAIL\_PASSWORD=

MAIL\_ENCRYPTION=tls

MAIL\_FROM\_ADDRESS="hello@yourdomain.com"

MAIL\_FROM\_NAME="\${APP\_NAME}"

AWS\_ACCESS\_KEY\_ID=

AWS\_SECRET\_ACCESS\_KEY=

AWS\_DEFAULT\_REGION=us-east-1

AWS\_BUCKET=

AWS\_USE\_PATH\_STYLE\_ENDPOINT=false

PUSHER\_APP\_ID=

PUSHER\_APP\_KEY=

PUSHER\_APP\_SECRET=

PUSHER\_HOST=

PUSHER\_PORT=443

PUSHER\_SCHEME=https

PUSHER\_APP\_CLUSTER=mt1

VITE\_APP\_NAME="\${APP\_NAME}"

VITE\_PUSHER\_APP\_KEY="\${PUSHER\_APP\_KEY}"

VITE\_PUSHER\_HOST="\${PUSHER\_HOST}"

VITE\_PUSHER\_PORT="\${PUSHER\_PORT}"

```
VITE_PUSHER_SCHEME="${PUSHER_SCHEME}"
```

```
VITE_PUSHER_APP_CLUSTER="${PUSHER_APP_CLUSTER}"
```